


Rotule GE SB9515082-IKO - SB9515082-IKO

<https://www.123roulement.be/roulement-palier/rotule/ge/sb9515082-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass. (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree	
	d	D	B	C	d_k	r_1	r_2	α		
95	SB 9515082		6.05	95	150	82	70	140	0.6	5
Mounting dimensions mm			Dynamic load capacity		Static load capacity					
d_s	D_s	C_d	C_d		C_s					
Min.	Max. ⁽²⁾	Min.	N		N					
99.5	113.5	145.5	130		961 000		5 770 000			

Notes:
(1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952391519
Diam. intérieur	95 mm
Diam. extérieur	150 mm
Épaisseur	82 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE