


Rotule GE GE120GS-IKO - GE120GS-IKO

<https://www.123roulement.be/roulement-palier/rotule/ge/ge120gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α ₁
120	GE 120GS		15.5	120	210	115	70	180	1	1	16	15
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s								
d _s		D _s		N		N						
Min.	Max.(2)	Max.	Min.									
125.5	138.5	204.5	176	1 240 000		7 410 000						

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952392547
Diam. intérieur	120 mm
Diam. extérieur	210 mm
Épaisseur	115 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE