

## Rotule GE SBB44-2RS-IKO - SBB44-2RS-IKO

<https://www.123roulement.be/roulement-palier/rotule/ge/sbb44-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>
<b>69.850</b> (2 3/4)		<b>SBB 44-2RS</b>	2.44	69.850 (2 3/4)	111.125 (4 3/8)	61.11 (2.406)	52.37 (2.062)
<i>d<sub>k</sub></i>	Radial internal clearance mm		Mounting dimensions mm		Dynamic load capacity <i>C<sub>d</sub></i> N	Static load capacity <i>C<sub>s</sub></i> N	
	Min.	Max.	<i>d<sub>1</sub></i>	<i>r<sub>1</sub></i> Max. <sup>(1)</sup> <sub>(2)</sub>			
100(3.937)	0.10	0.20	79.0	0.6	0.8	514 000	3 080 000

Notes: (1) Minimum allowable value of chamfer dimensions *r<sub>1</sub>* and *r<sub>2</sub>*.  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of *d<sub>k</sub>*.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952392912
Diam. intérieur	69.85 mm
Diam. extérieur	111.125 mm
Épaisseur	61.11 mm
Type	GE
Lubrification	sans
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE