


Rotule GE SBB56-2RS-IKO - SBB56-2RS-IKO

<https://www.123roulement.be/roulement-palier/rotule/ge/sbb56-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
88.900 (3 1/2)		SBB 56-2RS	4.83	88.900 (3 1/2)	139.700 (5 1/2)	77.77 (3.062)	66.68 (2.625)
d_k	Radial internal clearance mm		Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N	
	Min.	Max.	d_1	r_1 max. (¹) Max.			
128(5.039)	0.13	0.23	101.6	0.6	0.8	837 000	5 020 000

Notes: (¹) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(²) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952392974
Diam. intérieur	88.9 mm
Diam. extérieur	139.7 mm
Épaisseur	77.77 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE