



Rotule GE SBB72-2RS-IKO - SBB72-2RS-IKO

<https://www.123roulement.be/roulement-palier/rotule/ge/sbb72-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series

SBB--2RS Permissible tilting angle
SBB--2RS

Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
114.300 (4 1/2)		SBB 72-2RS	9.94	114.300 (4 1/2)	177.800 (7)	100.00 (3.937)	85.72 (3.375)
Radial internal clearance mm Min./Max.	Mounting dimensions mm			Dynamic load capacity C _d N	Static load capacity C _s N		
	d _k	d ₁	r ₁ max. r ₂ max.			C _d	C _s
164 (6.457)	0.13 / 0.23	129.8	0.8 1.1	1 380 000	8 270 000		

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952393056
Diam. intérieur	114.3 mm
Diam. extérieur	177.8 mm
Épaisseur	100 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE