


## Galet de roulement CRY16-V-IKO - CRY16-V-IKO

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/galet-roulement/cry16-v-iko>

**IKO**  
**ROLLER FOLLOWERS**  
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



Shaft dia. mm (inch)	Identification number		Max (Ref.) g	Boundary dimensions: mm(inch)			
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C
7.938 ( $\frac{5}{16}$ )	<b>CRY 16 V</b>		68	7.938   ( $\frac{5}{16}$ )	25.400   1	17.463   (0.6875)	15.875   ( $\frac{5}{8}$ )
		Shaft dia.				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>
		Push fit		Drive fit		Press fit	
		Min.	Max.	Min.	Max.	Min.	Max.
		19.60   (772)	1.191   ( $\frac{1}{8}$ )	7.920	7.930	7.935	7.945
						7.940	7.950
						13 100	22 700

Remarks: 1. The inner ring has an oil hole.  
2. Provided with prepacked grease.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952398068
Diam. intérieur	7.938 mm
Diam. extérieur	25.4 mm
Épaisseur	17.463 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE