

## Galet de roulement CRY24-VR-IKO - CRY24-VR-IKO

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/galet-roulement/cry24-vr-iko>

**IKO**  
**ROLLER FOLLOWERS**  
Non-separable Roller Followers, Inch Series Full Complement Type /With Inner Ring



Shaft dia. mm (inch)	Identification number		Max (Ref.) g	Boundary dimensions: mm(inch)				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>				
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C						
<b>11.112</b> ( $\frac{1}{2}$ )	<b>CRY 24 VR</b>		186	11.112 ( $\frac{1}{2}$ )	38.100 (1 $\frac{1}{2}$ )	23.813(0.9375)	22.225 ( $\frac{7}{8}$ )						
				Shaft dia.									
				Push fit		Drive fit		Press fit					
				Min.	Max.	Min.	Max.	Min.	Max.				
				28.8(1.134)	500 (20)	11.095	11.105	11.110	11.120	11.115	11.125	28 200	40 100

Remarks: 1. The inner ring has an oil hole.  
2. Provided with prepacked grease.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952398839
Diam. intérieur	11.112 mm
Diam. extérieur	38.1 mm
Épaisseur	23.813 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE