

## Roulement conique T2EE060-JTEKT - T2EE060-KOYO

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/t2ee060-koyo>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	r	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.					
60	115	40	39	33	2.5	183	242	3 400	4 600	T2EE060				
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>a</sub> min.	d <sub>a</sub> max.	D <sub>a</sub> min.	D <sub>a</sub> max.	S <sub>a</sub> min.	S <sub>a</sub> max.	r <sub>a</sub> min.	r <sub>a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2EE	27.6	72	70	103	98	109	6	7	2	2	0.33	1.80	0.99	1.80

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952406022
Diam. intérieur	60 mm
Diam. extérieur	115 mm
Épaisseur	40 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE