


## Roulement conique 32926-JR-JTEKT - 32926-JR-KOYO

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/32926-jr-koyo>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                     |                     | Basic load ratings (kN) |                     | Limiting speeds (min <sup>-1</sup> ) |                     | Bearing No. <sup>1)</sup> |            |                                   |                                   |                      |      |
|--|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|--------------------------------------|---------------------|---------------------------|------------|-----------------------------------|-----------------------------------|----------------------|------|
| d                                      | D                  | T                        | B                   | C                   | C <sub>r</sub>          | C <sub>0r</sub>     | Grease lub.                          | Oil lub.            |                           |            |                                   |                                   |                      |      |
| 130                                    | 180                | 32                       | 32                  | 25                  | 200                     | 368                 | 1 900                                | 2 500               | 32926JR                   |            |                                   |                                   |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                     |                     |                         |                     |                                      |                     |                           |            |                                   |                                   |                      |      |
|  |                    | d <sub>1</sub> min.      | d <sub>2</sub> max. | D <sub>1</sub> max. | D <sub>2</sub> min.     | S <sub>a</sub> min. | S <sub>b</sub> min.                  | r <sub>a</sub> max. | r <sub>b</sub> max.       | Constant e | Axial load factors Y <sub>1</sub> | Axial load factors Y <sub>0</sub> | (Refer. 1) Mass (kg) |      |
| 20C                                    | 31.4               | 140                      | 141                 | 171                 | 165                     | 174                 | 6                                    | 7                   | 2                         | 1.5        | 0.34                              | 1.77                              | 0.97                 | 2.42 |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 4549250125669 |
| Diam. intérieur | 130 mm        |
| Diam. extérieur | 180 mm        |
| Epaisseur       | 32 mm         |
| Conditionnement | 1             |
| Norme           | Sans norme    |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE