


## Roulement conique 28158-28300-JTEKT - 28158-28300-KOYO

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/28158-28300-koyo>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
40.000	76.200	20.638	20.940	15.507	1.6	1.2	57.3	65.9	5 300	7 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
28158	28300	16.5	47.5	45.0	68.0	71.0	1.6	1.2	0.40	1.49	0.82	0.266	0.137

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250107252
Diam. intérieur	40 mm
Diam. intérieur	1.575" inch
Diam. extérieur	76.2 mm
Diam. extérieur	3" inch
Epaisseur	20.638 mm
Epaisseur	13/16" inch
Poids	412 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE