


Galet de came avec axe CF18-UU-IKO - CF18-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cf18-uu-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF--UU

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
18				CF 18 UU	250	40	20	18	M18×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum ignoring stress N-mm	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	G ₁	G ₂	r _{max}	(°)					
19	21.6max	58.1max	36.5	8	0.8	6	3	1	29	86.2	14 800	25 200	25 200	

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952441399
Diam. intérieur	18 mm
Diam. extérieur	40 mm
Épaisseur	20 mm
Conditionnement	-

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE