


Galet de came avec axe CF30-UU-IKO - CF30-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cf30-uu-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30				CF 30 UU	1 870	80	35	30	M30×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N	
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _{max}	(°)						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952441597
Diam. intérieur	30 mm
Diam. extérieur	80 mm
Épaisseur	35 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE