


Galet de came avec axe CFES10-1-BUUR-IKO - CFES10-1-BUUR-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfes10-1-buur-iko>



CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers With Cage/With Hexagon Hole



CFES-BUUR

| Stud dia. mm | Identification number | | | | | | | | Mass (Ref.) g | D | C | d ₁ | | | |
|--------------------------|----------------------------|----------|--------------------------------|----------------|----------------------------|----------------|--------------------------------|----------------|---------------------|--------------------------------------|------------------------------------------|----------------------------------------|----------------------------------------|----------------------------------------------------|------------------------------------------|
| | Shield type | | | | Sealed type | | | | | | | | | | |
| | With crowned outer ring | | With cylindrical outer ring | | With crowned outer ring | | With cylindrical outer ring | | | | | | | | |
| 10 | CFES 10-1 BUUR | | | | | | | | 60 | 26 | 12 | 10 | | | |
| Boundary dimensions (mm) | | | | | | | | | | | | | | | |
| G | G ₁ | B max | B ₁ max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | H | ε ⁽¹⁾ K _{max} | Mounting dimension f Min. mm | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
| M10×1.25 | 12 | 13.2 | 36.2 | 23 | — | 0.6 | — | 4 | 0.3 | 0.3 | 16 | 13.8 | 5 430 | 6 890 | 6 890 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952443508 |
| Diam. intérieur | 10 mm |
| Diam. extérieur | 26 mm |
| Epaisseur | 12 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE