


Galet de came avec axe CFE24-1-B-IKO - CFE24-1-B-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe24-1-b-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers With Cage/With Hexagon Hole



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33	CFE 24-1 B				1 220	72	29	33

Boundary dimensions, mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	G ₁	H	H _{max}	H _{min}						
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	12	1	0.8	40	215	30 500	52 600	52 000

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060459589
Diam. intérieur	33 mm
Diam. extérieur	72 mm
Épaisseur	29 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE