


Galet de came avec axe CFE12-UU-IKO - CFE12-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe12-uu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



CFE12-UU

| Outside diameter of eccentric roller, mm | Identification number | | | | Mass (Ref.) | | | | |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|---|---|----------------|-----------|
| | Shield type | | Sealed type | | Ø | D | C | d ₂ | |
| 16 | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | CFE 12 UU |

| Boundary dimensions, mm | | | | | | | | | | Eccentricity g | Mounting dimension f mm | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|-------------------------|----------------|----------|-----------------------|----------------|----------------|----------------|----------------|-------------------------|-----|-------------------|-------------------------------|--|--|--|--|
| G | B ₃ | B max | B ₁ max | B ₂ | C ₁ | g ₁ | G ₁ | (1) r _{max} | e | | | | | | |
| M12×1.5 | 11.5 | 15.2 | 40.2 | 25 | 0.6 | 6 | 13.5 | 0.6 | 0.8 | 21 | 21.9 | 7 910 | 9 790 | 9 790 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060459916 |
| Diam. intérieur | 16 mm |
| Diam. extérieur | 30 mm |
| Épaisseur | 14 mm |
| Poids | 105 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE