

## Galet de came avec axe CFE16-R-IKO - CFE16-R-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe16-r-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller, mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		$\emptyset$	D	C	$d_2$
22	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	190	35	18	22
CFE 16 R								

  

Boundary dimensions, mm										Mounting dimension $f$ , mm	Maximum tightening torque, N-m	Basic dynamic load rating, C, N	Basic static load rating, $C_0$ , N	Maximum allowable axial load, N
G	$B_3$	$B$ max	$B_1$ max	$B_2$	$C_1$	$g_1$	$G_1$	$r_{max}$	$e$					
M16×1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26	58.5	12 000	18 300	18 300

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060459961
Diam. intérieur	22 mm
Diam. extérieur	35 mm
Epaisseur	18 mm
Poids	190 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE