


Galet de came avec axe CFE24-UU-IKO - CFE24-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe24-uu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



CFE24-UU

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)					
	Shield type		Sealed type		g	D	C	d ₂		
33	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 24	UU	895	62	29	33

Boundary dimensions, mm										Eccentricity g	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₁ max	B ₂	C ₁	g ₁	G ₁	(1) r _{max}	e						
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	30 500	52 600	52 000	

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060460134
Diam. intérieur	33 mm
Diam. extérieur	62 mm
Épaisseur	29 mm
Poids	895 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE