

Galet de came avec axe CFE16-VBUUR-IKO - CFE16-VBUUR-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe16-vbuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole

| Outside diameter of eccentric roller mm | Identification number | | | | Mass (Ref.) | | | | | | | | | | |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|----------------|----|------------------------|-------------------------------|--------------------------------|-------------------------------------|---|------------------------------------|--------|--------|--------|
| | Shield type | | Sealed type | | g | D | C | d _e | | | | | | | |
| 22 | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | 193 | 35 | 18 | 22 | | | | | | | |
| CFE 16 VBUUR | | | | | | | | | | | | | | | |
| Boundary dimensions, mm | | | | | | | | | | | | | | | |
| G | B ₃ | B ₁ max | B ₂ max | C ₁ | G ₁ | H | f ^(*) mm | Mounting dimension f mm | Maximum splining torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N | | | |
| M16×1.5 | 15.5 | 19.6 | 52.1 | 32.5 | 0.8 | 6 | 17 | 6 | 0.6 | 0.8 | 26 | 58.5 | 20 700 | 37 600 | 23 200 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060460554 |
| Diam. intérieur | 22 mm |
| Diam. extérieur | 35 mm |
| Épaisseur | 18 mm |
| Poids | 193 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE