

Galet de came avec axe CFE24-VBUUR-IKO - CFE24-VBUUR-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe24-vbuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33			CFE 24	VBUUR	900	62	29	33

Boundary dimensions, mm										
G	B ₃	B ₂ max	B ₁ max	B ₂	C ₁	G ₁	H	H _{max} (¹)	f mm	Mounting dimension g
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	12	1	0.8

Mounting dimension f mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum ultimate static load N
40	215	46 600	92 000	52 000

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060460707
Diam. intérieur	33 mm
Diam. extérieur	62 mm
Épaisseur	29 mm
Poids	900 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE