

Galet de came avec axe CFE12-VUUR-IKO - CFE12-VUUR-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe12-vuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric axle mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _a
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
16	CFE 12 VUUR				107	30	14	16

Boundary dimensions mm														
G	B ₃	B _{max}	B ₁ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	Eccentricity E	Mounting diameter f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M12 × 1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	13 500	19 700	13 200

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060461032
Diam. intérieur	16 mm
Diam. extérieur	30 mm
Épaisseur	14 mm
Poids	107 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE