


Galet de came avec axe CFE20-V-IKO - CFE20-V-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe20-v-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric axle mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		g	D	C	d _e						
27	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	505	52	24	27						
CFE 20 V														
Boundary dimensions mm														
G	B ₃	B _{max}	B ₂ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	Excentricity E	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M20 × 1.5	19.5	25.6	66.1	40.5	0.8	8	21	1	0.8	34	119	33 200	64 500	37 500

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060461186
Diam. intérieur	27 mm
Diam. extérieur	52 mm
Épaisseur	24 mm
Poids	505 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE