

## Galet de came avec axe CFE24-V-IKO - CFE24-V-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cfe24-v-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric axle mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		g	D	C	d <sub>e</sub>						
33	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	900	62	29	33						
<b>CFE 24 V</b>														
Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>2</sub> max	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	f <sub>1</sub> min	Excentricity E	Mounting diameter f Min. mm	Maximum ignoring torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
M24 × 1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	46 800	92 000	52 000

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060461247
Diam. intérieur	33 mm
Diam. extérieur	62 mm
Épaisseur	29 mm
Poids	900 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE