

Galet de came avec axe CR12-BR-IKO - CR12-BR-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cr12-br-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole

CR12-BR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
9.525 ($\frac{3}{8}$)	CR 12	BR			35	19.050 ($\frac{3}{4}$)	12.700 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	$\frac{1}{4}$ -24	9.525 ($\frac{3}{8}$)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm(inch)	Maximum ignoring torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
14.2 (0.56)	22.225 ($\frac{7}{8}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	2.381 ($\frac{1}{8}$)	4.762 ($\frac{3}{16}$)	0.794 ($\frac{1}{16}$)	13.494 ($\frac{1}{2}$)	10.8	4 420	5 110

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462404
Diam. intérieur	9.525 mm
Diam. extérieur	19.05 mm
Epaisseur	12.7 mm
Poids	35 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE