


Galet de came avec axe CR16-B-IKO - CR16-B-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cr16-b-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole



CR16-B

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
11.112 ($\frac{7}{16}$)	CR 16 B				73	25.400 (1)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{7}{16}$)	$\frac{1}{2}$ -20	12.700 ($\frac{1}{2}$)
Boundary dimensions mm/inch										
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm/inch	Maximum spinning torque C	Basic dynamic load rating C ₀
17.3 (0.68)	25.400 (1)	8.250 ($\frac{1}{2}$)	0.794 ($\frac{1}{16}$)	4.782 ($\frac{3}{8}$)	3.175 ($\frac{1}{8}$)	6.350 ($\frac{1}{4}$)	1.191 ($\frac{1}{8}$)	17.859 ($\frac{5}{8}$)	17.4	8 910

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462480
Diam. intérieur	11.112 mm
Diam. intérieur	7/16" inch
Diam. extérieur	25.4 mm
Diam. extérieur	1" inch
Epaisseur	15.875 mm
Epaisseur	5/8" inch
Poids	73 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE