

Galet de came avec axe CR16-BUUR-IKO - CR16-BUUR-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cr16-buur-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole

CR16-BUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
11.112 ($\frac{3}{8}$)			CR 16	BUUR	73	25.400 (1)	15.875 (1/2)	11.112 (3/8)	3/8-20	12.700 (1/2)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/inch	Maximum spinning torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
17.3 (3/8)	25.400 (1)	8.250 (1/2)	0.794 (1/8)	4.782 (3/8)	3.175 (1/4)	6.350 (1/4)	1.191 (1/8)	17.859 (3/4)	17.4	8 910	10 800

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462497
Diam. intérieur	11.112 mm
Diam. extérieur	25.4 mm
Épaisseur	15.875 mm
Poids	73 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE