


## Galet de came avec axe CR18-UU-IKO - CR18-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cr18-uu-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
11.112 ( $\frac{7}{16}$ )			<b>CR 18</b>	<b>UU</b>	88	28.575 ( $\frac{1}{2}$ )	15.875 ( $\frac{5}{8}$ )	11.112 ( $\frac{7}{16}$ )	$\frac{1}{8}$ -20	12.700 ( $\frac{1}{2}$ )
Boundary dimensions (mm)(inch)										
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	S <sub>1</sub>	S <sub>2</sub>	r	Mounting dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C <sub>0</sub> N	Basic static load rating C <sub>0</sub> N
17.3 (0.68)	25.400 (1)	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	3.175 ( $\frac{1}{8}$ )	1.588 ( $\frac{1}{16}$ )	19.050 ( $\frac{3}{4}$ )	17.4	9 190	11 600

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462978
Diam. intérieur	11.112 mm
Diam. extérieur	28.575 mm
Épaisseur	15.875 mm
Poids	88 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE