

Galet de came avec axe CR16-VBR-IKO - CR16-VBR-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cr16-vbr-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Screwdriver Slot

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G UNF | G ₁ | | | |
|------------------------------|---|---|---|---|---------------------|--------------------------|--------------------------|---------------------------|-------------------|--|--|--|--|
| | Shield type With cover outer ring | Shield type With cylindrical outer ring | Sealed type With cover outer ring | Sealed type With cylindrical outer ring | | | | | | | | | |
| 11.112 ($\frac{7}{16}$) | CR 16 | VBR | | | 74 | 25.400 ($\frac{1}{1}$) | 15.875 ($\frac{5}{8}$) | 11.112 ($\frac{7}{16}$) | $\frac{1}{2}$ -20 | 12.700 ($\frac{1}{2}$) | | | |
| Boundary dimensions mm(inch) | | | | | | | | | | Mounting dimension f Min. mm(inch) | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
| B max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | H | r | 17.3 (0.68) | 17.4 | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060463586 |
| Diam. intérieur | 11.112 mm |
| Diam. extérieur | 25.4 mm |
| Epaisseur | 15.875 mm |
| Poids | 74 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE