


Galet de came avec axe CR24-VB-IKO - CR24-VB-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cr24-vb-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR-VB

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G | G ₁ | |
|------------------------------|---|---|---|---|-------------------------|--------------------------|--------------------------|--|--|--|--|
| | Shield type With cover outer ring | Shield type With cylindrical outer ring | Sealed type With cover outer ring | Sealed type With cylindrical outer ring | | | | | | | |
| 15.875 ($\frac{5}{8}$) | | CR 24 VB | | | 230 | 38.100 ($\frac{1}{2}$) | 22.225 ($\frac{7}{8}$) | 15.875 ($\frac{5}{8}$) | $\frac{1}{4}$ -18 | 19.050 ($\frac{3}{4}$) | |
| Boundary dimensions mm(inch) | | | | | | | | | | | |
| B max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | H | r | Mounting dimension f Min. mm(inch) | Maximum tightening torque N-m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
| 23.8 (0.93) | 38.100 ($\frac{1}{2}$) | 9.525 ($\frac{3}{8}$) | 0.794 ($\frac{1}{16}$) | 4.762 ($\frac{3}{16}$) | 3.969 ($\frac{1}{4}$) | 7.938 ($\frac{1}{2}$) | 1.588 ($\frac{1}{16}$) | 26.195 ($\frac{1}{2}$) | 55.7 | 29 200 | 40 100 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060463913 |
| Diam. intérieur | 15.875 mm |
| Diam. extérieur | 38.1 mm |
| Épaisseur | 22.225 mm |
| Poids | 230 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE