

Galet de came avec axe CR28-VBUUR-IKO - CR28-VBUUR-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cr28-vbuur-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

CR28-VBUUR

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G UNF | G ₁ | |
|------------------------------|---|---|---|---|-------------------------|----------------------------|--------------------------|--|--|--|--|
| | Shield type With cover outer ring | Shield type With cylindrical outer ring | Sealed type With cover outer ring | Sealed type With cylindrical outer ring | | | | | | | |
| 19.050 ($\frac{3}{8}$) | | | CR 28 | VBUUR | 372 | 44.450 ($1\frac{7}{16}$) | 25.400 (1) | 19.050 ($\frac{3}{8}$) | $\frac{1}{4}$ -16 | 22.225 ($\frac{7}{8}$) | |
| Boundary dimensions mm(inch) | | | | | | | | | | | |
| B max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | H | r | Mounting dimension f Min. mm(inch) | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
| 25.8106 | 44.450 ($1\frac{7}{16}$) | 11.112 ($\frac{5}{8}$) | 0.794 ($\frac{1}{16}$) | 4.792 ($\frac{3}{16}$) | 3.969 ($\frac{1}{8}$) | 7.938 ($\frac{5}{16}$) | 1.588 ($\frac{1}{16}$) | 32.543 ($1\frac{1}{8}$) | 100 | 35 300 | 55 600 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060464088 |
| Diam. intérieur | 19.05 mm |
| Diam. extérieur | 44.45 mm |
| Epaisseur | 25.4 mm |
| Poids | 372 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE