


Galet de came avec axe CR36-VBUU-IKO - CR36-VBUU-IKO

<https://www.123roulement.be/roulement-palier/roulement-bille/galet-came-axe/cr36-vbuu-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR36-VBUU

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G UNF | G ₁ | | | |
|-------------------------------|---|---|---|---|--------------------------|---------------------------|---------------------------|---------------------------|----------|---|--------------------------------------|--|--|
| | Shield type With cover outer ring | Shield type With cylindrical outer ring | Sealed type With cover outer ring | Sealed type With cylindrical outer ring | | | | | | | | | |
| 22.225 ($\frac{7}{8}$) | | | CR 36 | VBUU | 759 | 57.150 (2 $\frac{1}{2}$) | 31.750 (1 $\frac{1}{4}$) | 22.225 (7/8) | 7-14 | 25.400 (1) | | | |
| Boundary dimensions mm (inch) | | | | | | | | | | Mounting dimension f Min. mm (inch) | Maximum spinning torque N-m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
| B max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | H | r | | | | | | |
| 33.5 (1.32) | 50.800 (2) | 12.700 (1/2) | 0.794 ($\frac{1}{32}$) | 4.762 ($\frac{3}{16}$) | 4.762 ($\frac{3}{16}$) | 11.112 (1/2) | 1.588 ($\frac{1}{16}$) | 37.305 (1 $\frac{3}{8}$) | 162 | 45 700 | 80 600 | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060464323 |
| Diam. intérieur | 22.225 mm |
| Diam. extérieur | 57.15 mm |
| Epaisseur | 31.75 mm |
| Poids | 759 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE