

## Roulement à aiguilles BHTM1616A-JTEKT - BHTM1616A-KOYO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bhtm1616a-koyo>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0e}$	Oil lub.
16	24	16	13.3	12.2	14.9	21 000
						Caged type With open ends    With closed end <b>BHTM1616A</b>

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (f6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	23.991 <sup>4)</sup>	24.012 <sup>4)</sup>	20	23

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952470368
Diam. intérieur	16 mm
Diam. extérieur	24 mm
Épaisseur	16 mm
Poids	20 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE