


Roulement à rouleaux NQI28-20-JTEKT - NQI28-20-KOYO

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nqi28-20-koyo>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.		
F_w	d	D	B	B_{10}	C_r	C_{10}	Oil lub.	Without inner ring	Without inner ring		
32	28	42	20	—	24.3	39.4	14 000	—	—		
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
With inner ring					Without inner ring	With inner ring					
NQI28/20					30	40	0.3	0.070	0.098	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482781
Diam. intérieur	28 mm
Diam. extérieur	42 mm
Épaisseur	20 mm
Poids	98 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE