

Roulement à rouleaux NQS55-22-JTEKT - NQS55-22-KOYO

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nqs55-22-koyo>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	B ₁	C _r	C _{0r}	Oil lub.		Without inner ring
55	45	72	22	—	44.6	71.6	8 300		NQS55/22
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring					Without inner ring	With inner ring			
	d ₁	D ₁	r ₁	r	0.210	0.341			—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483504
Diam. intérieur	55 mm
Diam. extérieur	72 mm
Épaisseur	22 mm
Poids	210 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE