


Roulement à rouleaux NA5920-JTEKT - NA5920-KOYO

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na5920-koyo>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	B ₁	C _r	C ₁₀	Oil lub.	—	Without inner ring
115	100	140	54	—	189.0	418.0	4 000	—	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		With inner ring	d ₁ min.	D ₁ max.	r _s max.	Without inner ring	With inner ring		
		NA5920	106.5	133.5	1	1.49	2.53	IRM1001554	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952484242
Diam. intérieur	100 mm
Diam. extérieur	140 mm
Épaisseur	54 mm
Poids	2530 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE