

Butée à aiguilles NTB130170-IKO - NTB130170-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/butee-aiguille/ntb130170-iko>

IKO
THRUST BEARINGS
Thrust Needle Roller Bearings

Shaft dia. mm	Identification number						
	Thrust needle roller bearing	Mass (Ref.) g	Thrust washer	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
130	NTB 130170	225	—	—	WS 130170	GS 130170	660

Boundary dimensions mm							Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
d	D	s	B	r _s min	C ₁	C ₂			
130	170	5	9	1	137	165	120 000	839 000	1 700

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension F
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952486574
Diam. intérieur	130 mm
Diam. extérieur	170 mm
Épaisseur	5 mm
Poids	225 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE