

Rondelle de butée WS110160-IKO - WS110160-IKO

<https://www.123roulement.be/accessoire/rondelle/rondelle-butee/ws110160-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings

Shaft dia. mm	Identification number										Inner ring Mass (Ref.) g	Outer ring Mass (Ref.) g	Mass (Ref.) g
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring		Outer ring		Mass (Ref.) g				
110	AZ 11016040	3 220	AZK 11016017	1 320	WS 110160	GS 110160			950				

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
d	D	T	d _c	D _c	D _w	B	r	d ₁	D ₁	d ₂ Min.	D ₂ Max.			
110	160	40	110.1	159.5	17	11.5	1.1	120	154	153	121	282 000	1 030 000	2 000

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060466983
Diam. intérieur	110 mm
Diam. extérieur	160 mm
Épaisseur	11.5 mm
Matière	ACIER
Poids	950 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE