


Rotule SI
DSIL5-T-K-DURBAL - DSIL5-T-K-DURBAL
<https://www.123roulement.be/roulement-palier/rotule/si/dsil5-t-k-durbal>

DSIL5-T-K

female thread: maintenance free, according to DIN ISO 12240-4, series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Red end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4	
DSIL 5 T/K		5	M 5	8	6,00	18	8,5	11	

type	measurement [mm]			load rating C0 [N]	weight [g]	
	l1 min	W	h			
DSI / DSIL 5 T/K	10	9	27	13	6,0	0,016

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489070
Diam. intérieur	5 mm
Diam. extérieur	18 mm
Epaisseur	8 mm
Type	SI
Poids	16 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE