

Rotule SI

DSIL5-T-K-DURBAL - SIL5-T-K-DURBAL

https://www.123roulement.be/roulement-palier/rotule/si/sil5-t-k-durbal


DSIL5-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
DSIL	S T/K	5	M 5	8	6,00	18	8,5	11

type	measurement (mm)			h	d ₁	load rating C ₀ (N)	weight (kg)
	l ₁ min	W					
DSI / DSIL	S T/K	10	9	27	13	6,0	0,016

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489070
Diam. intérieur	5 mm
Diam. extérieur	18 mm
Epaisseur	8 mm
Type	SI
Poids	16 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE