


Rotule SI
SIL6-T-K-DURBAL - SIL6-T-K-DURBAL
<https://www.123roulement.be/roulement-palier/rotule/si/sil6-t-k-durbal>

SIL6-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Steel end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 6 T/K		6	M 6	9	6,75	20	10,0	13

type	measurement [mm]			load rating C ₁₀ [N]	weight [g]
	l ₃ min	W	h		
SI / SIL 6 T/K	12	11	30	7,7	0,022

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489117
Diam. intérieur	6 mm
Diam. extérieur	20 mm
Epaisseur	9 mm
Type	SI
Poids	22 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE