

Rotule SI DSIL18-T-K-DURBAL - DSIL18-T-K-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/dsil18-t-k-durbal>


DSIL18-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
DSIL 18 T/K			18	M 18 x 1,5	23	16,50	44	25,0	31

type	measurement (mm)			h	d1 PT	load rating C0 [N]	weight [kg]
	l3 min	W					
DSI / DSIL 18 T/K	32	27	71	15		47,5	0,320

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489506
Diam. intérieur	18 mm
Diam. intérieur	0.709" inch
Diam. extérieur	44 mm
Diam. extérieur	1.732" inch
Epaisseur	23 mm
Epaisseur	0.906" inch
Type	SI
Poids	320 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE