

Rotule SI

SIL35-T-K-DURBAL - SIL35-T-K-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/sil35-t-k-durbal>


SIL35-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
	SIL 35 T/K	35	M 36 x 2	43	28,00	81	46,0	58

type	measurement [mm]			h	d ₁ PT	load rating C ₀ [kN]	weight [kg]
	l ₁ min	W					
SI / SIL 35 T/K	56	50		125	16		1,600

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952489803
Diam. intérieur	35 mm
Diam. intérieur	1.378" inch
Diam. extérieur	81 mm
Diam. extérieur	3.189" inch
Epaisseur	43 mm
Epaisseur	1.693" inch
Type	SI
Poids	1600 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE