

Rotule SA


SAL20-T-K-DURBAL - SAL20-T-K-DURBAL

https://www.123roulement.be/roulement-palier/rotule/sa/sal20-t-k-durbal

SAL20-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 20 T/K	20	M 20 x 1,5	25	18,00	50

type	measurement [mm]				Tragzahlen C ₁₀ [KN]	weight [kg]
	l ₁ min	l ₂	h	α [°]		
SA / SAL 20 TIK	45	25	78	14	57,0	0,380

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490243
Diam. intérieur	20 mm
Diam. extérieur	50 mm
Épaisseur	25 mm
Type	-
Poids	380 g
Filetage	-
Lubrification	-
Conditionnement	-
Norme	-

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE