


Rotule SA
SAL28-T-K-DURBAL - SAL28-T-K-DURBAL
<https://www.123roulement.be/roulement-palier/rotule/sa/sal28-t-k-durbal>

SAL28-T-K

male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Red end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 28 T/K		28	M 27 x 2	35	24,00	66

type	measurement [mm]			α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SAL 28 T/K	62	33	103	15	107,0	0,800

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490335
Diam. intérieur	28 mm
Diam. extérieur	66 mm
Epaisseur	35 mm
Type	SA
Poids	800 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE