

Rotule SA SSAL22-T-K-DURBAL - SSAL22-T-K-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/sa/ssal22-t-k-durbal>

SSAL22-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	right hand thread	left hand thread	d	G	measurement [mm]	B	C1	d2
SSAL 22 T/K			22	M 22 x 1,5		28	20,00	54

type	measurement [mm]			h	alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min					
SSA / SSAL 22 T/K	48	27	84	15	68,0	0,480	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490908
Diam. intérieur	22 mm
Diam. extérieur	54 mm
Epaisseur	28 mm
Type	SA
Poids	480 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE