

# Rotule SI

## DSSI6-T-K-DURBAL - DSSI6-T-K-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/dssi6-t-k-durbal>

### DSSI6-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | right hand thread | left hand thread | measurement [mm] |     |   |      |    |      |    |    |
|--------------|-------------------|------------------|------------------|-----|---|------|----|------|----|----|
| DSSI 6 T/K   |                   |                  | d                | G   | B | C1   | d1 | d2   | d3 | d4 |
|              |                   |                  | 6                | M 6 | 9 | 6,75 | 20 | 10,0 | 13 |    |

| type               | l1 min | W  | h  | α  | load rating<br>C0<br>[kN] | weight<br>[g] |
|--------------------|--------|----|----|----|---------------------------|---------------|
| DSSI / DSSIL 6 T/K | 12     | 11 | 30 | 13 | 7,7                       | 0,022         |

## CARACTÉRISTIQUES PRODUIT

|                 |                   |
|-----------------|-------------------|
| Marque          | DURBAL            |
| N° Ean13        | 3663952491127     |
| Diam. intérieur | 6 mm              |
| Diam. extérieur | 20 mm             |
| Epaisseur       | 9 mm              |
| Type            | SI                |
| Poids           | 22 g              |
| Filetage        | Filetage à droite |
| Lubrification   | sans              |
| Conditionnement | 1                 |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE