

Rotule SI

DSSIL12-T-K-DURBAL - DSSIL12-T-K-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/dssil12-t-k-durbal>

DSSIL12-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 12 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			12	M 12	16	12,00	32	17,5	22	

type	l ₁ min	W	h	α	load rating C ₀ [kN]	weight [kg]
DSSi / DSSIL 12 T/K	22	19	50	13	24,0	0,100

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491264
Diam. intérieur	12 mm
Diam. extérieur	32 mm
Epaisseur	16 mm
Type	SI
Poids	100 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE