

Rotule SI

SSIL16-T-K-DURBAL - SSIL16-T-K-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/ssil16-t-k-durbal>

SSIL16-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | right hand thread | left hand thread | measurement [mm] | | | | | | |
|--------------|-------------------|------------------|------------------|-------|----|------|----|--|--|
| SSIL 16 TIK | 16 | M 16 | 21 | 15,00 | 42 | 22,0 | 27 | | |

| type | l ₁ min | W | h | α | load rating C ₀ [kN] | weight [g] |
|-------------------|--------------------|----|----|----|---------------------------------|------------|
| SSI / SSIL 16 TIK | 28 | 22 | 64 | 15 | 39,0 | 0,220 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952491417 |
| Diam. intérieur | 16 mm |
| Diam. extérieur | 42 mm |
| Epaisseur | 21 mm |
| Type | SI |
| Poids | 220 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE