

Rotule SI

SSI22-T-K-DURBAL - SSI22-T-K-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/ssi22-t-k-durbal>

SSI22-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	right hand thread	left hand thread	measurement [mm]							
SSI 22 T/K			d	G	B	C1	d1	d2	d3	d4
			22	M 22 x 1,5	28	20,00	54	30,0		38

type	measurement [mm]			α °	load rating C ₀ (kg)	weight P ₀ (g)
	l ₁ min	W	h			
SSI / SSIL 22 T/K	37	32	84	15	68,0	0,540

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491608
Diam. intérieur	22 mm
Diam. intérieur	0.866" inch
Diam. extérieur	54 mm
Diam. extérieur	2.126" inch
Epaisseur	28 mm
Epaisseur	1.102" inch
Type	SI
Poids	540 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE