

# Rotule SI

## DSIL12-PK-DURBAL - DSIL12-PK-DURBAL

<https://www.123roulement.be/roulement-palier/rotule/si/dsil12-pk-durbal>

### DSIL12-PK



**female thread; maintenance free, according to DIN ISO 12240-4, series K**

**Description:** DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

**Rod end body:** surface case plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel hardened and ground

**Outer ring:** rod end body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	d	G	measurement (mm)				
right hand thread	12	M 12	16	12,00	33	17,5	22
<b>DSIL 12 PK</b>							

type	l <sub>1</sub> min	measurement (mm)			lead rating	weight
		W	h	α [°]	C <sub>0</sub> (N)	(kg)
<b>DSI / DSIL 12 PK</b>	22	19	50	13	24,00	0,100

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491974
Diam. intérieur	12 mm
Diam. extérieur	33 mm
Epaisseur	16 mm
Type	SI
Poids	100 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE