


Rotule SA
DSA8-BK-DURBAL - DSA8-BK-DURBAL
<https://www.123roulement.be/roulement-palier/rotule/sa/dsa8-bk-durbal>

DSA8-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel hardened and ground

Outer ring:
rod end body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
DSA 8 BK		8	M 8	12	9,0	25

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
DSA / DSAL 8 BK	25	42	12	12,90	0,038

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952492407
Diam. intérieur	8 mm
Diam. extérieur	25 mm
Epaisseur	12 mm
Type	SA
Poids	38 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE